


## GOPO 7W SPOT PLAFON



Plafón redondo con fuente de luz recedida y orientable. Regulacion 360°



potencia	ángulo	color (K)	flujo	eficiencia	dim	driver	código
7W	24°	2700K	410lm	59 lm/W	TRIAC	BUILT IN	02-AA95.2210.03
7W	24°	2700K	410lm	59 lm/W	TRIAC	BUILT IN	02-AA95.2210.06
7W	24°	3000K	410lm	59 lm/W	TRIAC	BUILT IN	02-AA95.2234.03
7W	24°	3000K	410lm	59 lm/W	TRIAC	BUILT IN	02-AA95.2234.06
7W	40°	2700K	410lm	59 lm/W	TRIAC	BUILT IN	02-AA95.2213.03
7W	40°	2700K	410lm	59 lm/W	TRIAC	BUILT IN	02-AA95.2213.06
7W	40°	3000K	410lm	59 lm/W	TRIAC	BUILT IN	02-AA95.2236.03
7W	40°	3000K	410lm	59 lm/W	TRIAC	BUILT IN	02-AA95.2236.06

## INFORMACIÓN TÉCNICA

CRI	>90
INDICE DE PROTECCIÓN	20
RESISTENCIA AL IMPACTO MECÁNICO	
CLASE	II
TENSIÓN	220-240

## INFORMACIÓN GENERAL

USO	
SUPERFICIE	Techo
ILUMINACIÓN	Directa
MEDIDAS	Ø115x78mm
CUT OUT	
PESO (KG)	0.42
REGULACIÓN	
COLOR	Blanco Texturado - Negro Texturado



bridge lux.



IP20

