


Empotrable con cabezales extraíbles. 2 luces.



potencia	ángulo	color (K)	flujo	eficiencia	dim	driver	código
2x3W	9°	2700K	450lm	75 lm/W	TRIAC	EXTERNO	06.78.3133.03
2x3W	9°	2700K	450lm	75 lm/W	TRIAC	EXTERNO	06.78.3133.06
2x3W	9°	3000K	450lm	75 lm/W	TRIAC	EXTERNO	06.78.3130.03
2x3W	9°	3000K	450lm	75 lm/W	TRIAC	EXTERNO	06.78.3130.06
2x3W	30°	2700K	450lm	75 lm/W	TRIAC	EXTERNO	06.78.3135.03
2x3W	30°	2700K	450lm	75 lm/W	TRIAC	EXTERNO	06.78.3135.06
2x3W	30°	3000K	450lm	75 lm/W	TRIAC	EXTERNO	06.78.3132.03
2x3W	30°	3000K	450lm	75 lm/W	TRIAC	EXTERNO	06.78.3132.06

#### INFORMACIÓN TÉCNICA

CRI	>90
INDICE DE PROTECCIÓN	20
RESISTENCIA AL IMPACTO MECÁNICO	
CLASE	II
TENSIÓN	220-240

#### INFORMACIÓN GENERAL

USO	
SUPERFICIE	Techo
ILUMINACIÓN	Directa
MEDIDAS	113X58X107mm
CUT OUT	100x50mm
PESO (KG)	
REGULACIÓN	
COLOR	Blanco Texturado - Negro Texturado



**CREE**

