


SHHH 3W MICRO UNI

Empotrable de con cabezal extraíble Ø58mm. 1 luz.



potencia	ángulo	color (K)	flujo	eficiencia	dim	driver	código
3W	9°	2700K	225lm	75 lm/W	TRIAC	EXTERNO	06.78.3103.03
3W	9°	2700K	225lm	75 lm/W	TRIAC	EXTERNO	06.78.3103.06
3W	9°	3000K	225lm	75 lm/W	TRIAC	EXTERNO	06.78.3100.03
3W	9°	3000K	225lm	75 lm/W	TRIAC	EXTERNO	06.78.3100.06
3W	30°	2700K	225lm	75 lm/W	TRIAC	EXTERNO	06.78.3105.03
3W	30°	2700K	225lm	75 lm/W	TRIAC	EXTERNO	06.78.3105.06
3W	30°	3000K	225lm	75 lm/W	TRIAC	EXTERNO	06.78.3102.03
3W	30°	3000K	225lm	75 lm/W	TRIAC	EXTERNO	06.78.3102.06

INFORMACIÓN TÉCNICA

CRI	>90
INDICE DE PROTECCIÓN	20
RESISTENCIA AL IMPACTO MECÁNICO	
CLASE	II
TENSIÓN	220-240

INFORMACIÓN GENERAL

USO	
SUPERFICIE	Techo
ILUMINACIÓN	Directa
MEDIDAS	Ø58x107mm
CUT OUT	Ø50mm
PESO (KG)	
REGULACIÓN	
COLOR	Blanco Texturado - Negro Texturado



CREE ⇄

